

AS964I

Avvisatore acustico serie 950, con isolatore incorporato multi tono autoalimentato dal loop. Protezione IP65. Colore rosso. EN54-3, EN54-17 CPD

General

The AS964I is a 950 series, intelligent loop powered open-area sounder in RED with a built in isolator. It is designed for use in indoor and outdoor open area applications. It supports 3 tones with two volume settings.

A locking mechanism is available to prevent unauthorized removal of the AS964I from its base.

Isolation and Maintenance

The AS964I sounder is supplied with an isolating base. A yellow LED on the base is illuminated if a loop short circuit is detected. All fault and abnormal conditions such as sounder failures are reported back to the panel for easy faultfinding.

Sounder Tone Support

That AS964I supports the following tones:

- Standard
- Slow Whoop (NEN2575)
- DIN (33404pt3)

Two volume settings are available in each tone variant.



Dettagli

- Self-test fault monitoring
- Multiple tones
- Alarm synchronisation
- Loop powered
- Including loop isolator

AS964I

**Avvisatore acustico serie 950, con isolatore incorporato multi tono autoalimentato dal loop.
Protezione IP65. Colore rosso. EN54-3, EN54-17 CPD**

Specifiche tecniche

Elettrico

Tensione di esercizio	17 to 28 VDC
-----------------------	--------------

Ambientale

Ambiente	Interno
----------	---------

IP rating	IP65
-----------	------

Regolatorio

Certificazioni	EN54-17, EN54-3
----------------	-----------------

Current consumption @ 24 VDC

Quiescent	< 333 μ A
-----------	---------------

Switch on surge (< 1 s)	< 1.2 mA
-------------------------	----------

Alarm (Sounder only)	5 mA
----------------------	------

Sounder frequency

Tone dependant

Sound output (max)

100 dB(A) @ 90° ($\pm$ 3dB(A))



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 22 May 2023 - 12:59