



Minidome IP AV, 4Mpxl, 3.3-12mm MOTOR., ICR, WDR(120dB), LEDs 20-30mt, IP66/IK10, PoE, VCA

- 4 Megapixel IP Camera with real time video streaming
- H265 for high compression rate and stable stream control
- Motorized varifocal lens for easy remote focusing
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- Vandal Resistant Dome (IK10)
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-V6321TI

Technical Specifications

Image Sensor	1/3" CMOS Progressive Scan OV4689
Pixels - Total	2688(H) x 1520 (V)
Video Resolution	1280x720 (720p), 1920x1080 (1080p), 3MP 2304 (H) x1296 (V), 4MP 2560 (H) x1440 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.05 Lux @ F1.2
Sensitivity B/W	0 Lux LED IR on, 0.01 lux @ F1.2
Lens Focal Length	3.3~12 mm Motorized Autofocus
Horizontal Viewing Angle	80° (Wide) ~ 38° (Tele)
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
ONVIF compliant	Profile S
Max. Users	10
SD memory	supports up to 64 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 OUT MIC
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP66
Firmware Upgrade	Firmware upgrade by Web Browser

Technical Specifications

Operating Temperature	-20°C ~ +50°C
Humidity	10 ~ 90%RH
Power Consumption (W)	5
Weight	1.260 kg - 2.78 lbs
Dimensions	Ø 150.11 mm - 5.91 In