

SEI-E7221TI-PA



Eyeball IP, 5MP, 2.8-12mm Motor., H.265+, ICR, WDR 120dB, LEDs 30-50mt, IP67,IK10, PoE, Advanced VCA B with Voice&Light Annunciation.

- 5 Megapixel resolution
- Advanced Analytics with car\human\bike classification
- Triple-streaming support
- Motorized varifocal lens for easy remote focusing
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.7" progressive scan CMOS
Pixels - Total	2592 (H) x 1944 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.008 lux @ (F1.4)
Lens Focal Length	2.8 ~ 12 mm, Motorized Autofocus
Iris F-Number	F= 1.4
S/N Ratio	>50 dB
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	MJPEG, Triple Streaming, H.265+/H.265/H.264+/H.264
Video Resolution	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps), 2048x1536 (25 fps), 5M 2592x1944 (20fps), 4M 2592x1520 (30fps)
Audio Inputs	1
Audio Outputs	Built-in speaker, Speaker Used to activated audio alarm in case of VCA intrusion
Alarm	Input: 1 / Output: 1
Advanced Video Analytics	Advanced video Analytics B: Area intrusion\line crossingwith Object Classification (Human, Vehicle, Bike)
ONVIF compliant	Profile S
Max. Users	4
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing

SEI-E7221TI-PA

**Technical Specifications**

Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	11,5
Weight	0.64 kg - 1.41 lbs
Dimensions	Ø 111.5 x 99.6 mm - 4.39 x 3.92 In