

# GS320

**Sensore piezo rottura vetri uscita a relè e memoria.**

## High Performance

---

The glassbreak detector GS320 with relay output is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm.

Suitable for use on standard window glass or plate glass the GS320 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard. They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



## Dettagli

---

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

# GS320

Sensore piezo rottura vetri uscita a relè e memoria.

## Specifiche tecniche

---

### Generale

Tecnologia	Piezo
Tipo di vetro	Lastra
Range	2 m radius
Tamper switch	No

### Cablato / senza fili

Wired-wireless	Cablato
----------------	---------

### Elettrico

Power supply value	9 to 18 VDC
Consumo attuale	4 mA @ 6 VDC 5 mA @ 12 VDC

### Fisico

Dimensioni fisiche	37 x 19 x 12 mm
Peso netto	50 g
Colore	Bianco
Tipo di montaggio	Montaggio a superficie

### Ambientale

Temperatura operativa	-25 to +70°C
IP rating	IP67

### Regolatorio

Certificazioni	EN50131 Grade 2, VdS
----------------	----------------------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita [it.firesecurityproducts.com](http://it.firesecurityproducts.com) online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:33