

SEI-P6620TIO



PTZ Dome Camera IP, 4MP, Starlight, 25x Zoom, IR LEDs 100mt, ICR, WDR, IP66, H.265, Autotracking, 12VDC/POE.

- 4MP Resolution
- STARLIGHT technology for extreme brilliant images in low light conditions
- 25x motorized optical zoom with 16x digital zoom
- Integrated IR LEDs 100mt range
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- High Speed Pan/Tilt (240°/sec Pan 160°/sec Tilt)
- Colour/B&W function with removable IR cut filter
- Operating Temperature (-30°C~ 60°C)

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-P6620TIO

Technical Specifications

Image Sensor	1/2,5" Progressive Scan CMOS
Scanning System	Progressive
Video Resolution	4MP 2560 (H) x1440 (V)
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity B/W	0 Lux LED IR on, 0.02 lux @ F1.6
Sensitivity Colour	0.1 lux @ F1.6
Lens Focal Length	4,8 ~ 120 mm
Optical Zoom Ratio	x 25
Lens Drive Type	Auto Iris (DC)
Max. IR Distance	100 m
Alarm Inputs	None
Alarm Outputs	None
S/N Ratio	>50 dB
White Balance	Auto / Manual
WDR	120dB, True WDR
DNR	Yes
Network Protocol	DHCP, TCP/IP, NTP, PPPoE, UDP, RTSP, SMTP, FTP, DDNS
Video Compression	H.264, H.265
Streaming	Triple Streaming
Alarm Notification	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
Network Interface	10/100 Base-T
Web Browser	All major browsers are supported
PTZ Control	3D Intelligent Position
Pan Speed	max. 240°/s
Tilt Speed	max. 160°/s
Range Panning	360° endless
Number of Preset	300
Number of Pattern	8
Privacy zones	4
Home position	Preset/Sequence/Auto Pan/Cruise
Auto Flip	Yes
OSD	Yes

Technical Specifications

Protection Rating	IP66
Surge protection maximum voltage	4 KV
Operating Temperature	-30°C ~ +55°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af), Power adaptor included
Accessories included	Bracket & PSU included
Power Consumption (W)	22
Weight	2.1 kg - 4.63 lbs
Dimensions	Ø 173 mm - 6.81 In