



Minidome PTZ IP, 2MP, 4x Zoom, IR LEDs 40mt, ICR, WDR, IP66, Poe, 12VDC.

- 2 Megapixel Minidome PTZ IP Camera Real Time Streaming
- 4x motorized optical zoom
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Colour/B&W function with removable IR cut filter
- Maximum range up to 40m

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-P4421BI

Technical Specifications

Image Sensor	1/3" Progressive Scan CMOS Sony Starlight IMX307
Scanning System	Progressive
Video Resolution	1920x1080
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Lens Focal Length	2.8 ~ 12 mm
Optical Zoom Ratio	4x
Lens Drive Type	Auto Iris (DC)
Max. IR Distance	40 m
Alarm Inputs	None
Alarm Outputs	None
Audio Inputs	None
Audio Outputs	None
Audio Compression	G.711 a/u
S/N Ratio	>50 dB
White Balance	Auto / Manual
AGC	Auto, Manual
Network Protocol	DHCP, TCP/IP, NTP, PPPoE, UDP, RTSP, SMTP, FTP, DDNS
Video Compression	H.264, MJPEG, H.265
Streaming	Dual Streaming
Alarm Notification	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
Network Interface	10/100 Base-T
Web Browser	All major browsers are supported
PTZ Control	3D Intelligent Position
Pan Speed	max. 120°/s
Tilt Speed	0.1 ~ 30°/s
Range Panning	350° limited Rotation
Number of Preset	220
Number of Pattern	3
Home position	Preset/Sequence/Auto Pan/Cruise
Auto Flip	Yes
OSD	Yes
Protection Rating	IP66

Technical Specifications

Surge protection maximum voltage	Transient voltage 6000V
Operating Temperature	-40°C ~ +60°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc
Power Consumption (W)	10
Weight	1.5 kg - 3.31 lbs
Dimensions	Ø 108 x 95 mm - 4.25 x 3.74 In