

**SER-7E0410TEF**

**XVR Ibrido 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 4 Channel + 2 IP (up to 6), 25fps@4MPlite/1080p/720p/960H o 20fps@5MPlite o 12fps@4KLite/5MP/4MP o 6fps@4K + 2 IP 4K/25fps/6Mbps, HDMI(4K)/VGA/SPOT, I/O, Fanless**

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Support up to 8MP Resolution Recording
- H265 for high compression rate and stable stream control
- Possibility to change the analog input into IP input
- Real-Time Recording @ 1080p
- Operating System - Linux Embedded
- Pentaplex: preview, record, playback, backup and remote access
- Free DDNS service

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Operating System</b>	Embedded Linux
<b>Basic Internal Storage</b>	0 GB
<b>Max. Storage Capacity</b>	1 Hard disk (3.5 inch SATA), up to 10TB
<b>External Backup</b>	USB Memory, Network
<b>Video Inputs</b>	4 CH 960H/HD-TVI/AHD/HD-CVI (BNC) + 2 CH IP, up to 6ch IP
<b>Video Outputs</b>	1x VGA, 1x HDMI, 1x BNC (spot out)
<b>Display resolution</b>	Up to 4K on HDMI, Up to 1920x1080 (HDMI / VGA)
<b>Video Compression</b>	H.264, H.265, Single/ Dual Stream for each channel
<b>Display Speed</b>	Real-time
<b>Recording Mode</b>	Continuous, Event Alarm, Motion, Schedule
<b>HDMI/VGA output</b>	4K, 4KLite, 5MP e 5MPLite (solo TVI-AHD), 4MP, 4MPLite, 1080P, 720P, 960H
<b>Recording Speed</b>	4K 6fps, 4KLite\5MP\4MP 12fps, 5MPLite 20fps, 4MPLite\1080p\720p 25fps
<b>Audio Inputs</b>	4 CH, RCA
<b>Audio Outputs</b>	1 CH, RCA
<b>Motion Detection</b>	On/ Off/ Area Setting
<b>Alarm Trigger</b>	Motion detection, Alarm Input, Video Loss, System Exceptions
<b>Alarm Notification</b>	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
<b>Alarm Inputs</b>	4
<b>Alarm Outputs</b>	1
<b>Interfaces</b>	RS-485, 2 x USB 2.0
<b>Serial Protocol</b>	Pelco D, Pelco P, ..., CoC (control over coax)
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Bandwidth</b>	Incoming 16Mbps, Outgoing 40Mbps
<b>Network Protocol</b>	DHCP, TCP/IP, PPPoE, UPnP, SMTP, NTP, HTTPS, DNS, DDNS, HTTP, IPv4/IPv6, RTSP, ONVIF, AutoDDNS, AutoNAT, QRCode
<b>Monitoring</b>	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
<b>Max. Users</b>	10
<b>Playback</b>	Synchronised playback of max. 4 cameras
<b>Search Mode</b>	Date/Time, Event Alarm, Motion, Video Loss
<b>Supply Voltage</b>	12 Vdc (230 Vac power adaptor included)

**SER-7E0410TEF****Technical Specifications**

<b>Operating Temperature</b>	-10°C ~ +50°C
<b>Humidity</b>	10 ~ 90%RH
<b>Dimensions ( W x H x D)</b>	300 x 45 x 249 mm - 11.81 x 1.77 x 9.8 In
<b>Power Consumption (W)</b>	10
<b>Weight</b>	3.1 kg - 6.83 lbs