

SEI-P8780TIO



PTZ Dome Camera IP, 8MP, Ultra-Starlight, 37x Zoom, IR LEDs 300mt, ICR, WDR 120db, IP67, IK10, H.265, Autotracking, 24 VAC/VDC, POE++, NDAA.

- 8MP Resolution
- Ultra STARLIGHT technology for extreme brilliant images in low light conditions
- 37x motorized optical zoom
- Integrated IR LEDs 300mt range
- Auto tracking
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Colour/B&W function with removable IR cut filter
- TVS 6KV lightning protection, surge protection

SEI-P8780TIO



Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/1.8" progressive scan CMOS
Scanning System	Progressive
Video Resolution	3840 × 2160 (25fps)
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity B/W	0 Lux LED IR on, 0.001 lux @ F1.6
Sensitivity Colour	0.1 lux @ F1.6, 0.005 lux @ F1.6
Lens Focal Length	6 ~ 222 mm
Optical Zoom Ratio	x 37
Lens Drive Type	Auto Iris (DC)
Max. IR Distance	300 m
Alarm Inputs	2
Alarm Outputs	2
S/N Ratio	>50 dB
White Balance	Auto / Manual
WDR	120dB, True WDR
DNR	Yes
Network Protocol	DHCP, TCP/IP, UPnP, PPPoE, HTTPS, SMTP, NTP, DNS, HTTP, DDNS, SNMP, IPv4/IPv6, RTP, UDP, QoS, RTSP, FTP, IEEE 802.1 X, RTCP
Video Compression	H.264, MJPEG, H.265, H.264+
Streaming	Triple Streaming
Alarm Notification	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
Network Interface	10/100 Base-T
Advanced Video Analytics	Advanced video Analytics B: Area intrusion/line crossing with Object Classification (Human, Vehicle, Bike), Autotracking
Web Browser	All major browsers are supported
PTZ Control	3D Intelligent Position
Pan Speed	0.1 ~ 240°/s
Tilt Speed	0.1 ~ 180°/s
Range Panning	360° endless
Number of Preset	300
Number of Pattern	8
Privacy zones	N.D
Home position	Preset/Sequence/Auto Pan/Cruise

SEI-P8780TIO



Technical Specifications

Auto Flip	Yes
OSD	Yes
Number of users	10 Simultaneous users
Protection Rating	IK10, IP67
Surge protection maximum voltage	Transient voltage 6000V
Operating Temperature	-40°C ~ +65°C
Humidity	less than 95%, non condensing
Supply Voltage	24 Vac, 24 Vdc, Power adaptor included, PoE++ (IEEE 802.3bt calss 6)
Accessories included	Bracket & PSU included
Power Consumption (W)	48
Weight	6 kg - 13.23 lbs
Dimensions	Ø 219.9 mm - 8.66 In