

BEST SELLER



# Cat 6A Punchdown Patch Panel, 24 Ports, 1 RU, BL

DP246X88TGY

PchDownPtchPnl,Cat6A,Flat,24-port,EA

## Specifications

Product Type	Patch Panel Kit
Termination Style	Punchdown
Patch Panel Style	Flat
Performance Level	Category 6A
Material	CRS
Wiring Scheme	T568A/T568B
Number of Ports	24
Number of Rack Units	1
Overall Width (In.)	19
Overall Width (mm)	482.6
Sub Brand	Pan-Net®
Overall Depth (In.)	1.17
Overall Depth (mm)	29.7
Overall Height (In.)	1.72
Overall Height (mm)	43.7
Identification Type	Adhesive Label
Color	Black
Standards Met	Exceeds component requirements of ANSI/TIA-568-C.2 Category 6A and ISO 11801 Class EA standards at swept frequencies 1 to 500 MHz, Exceeds component requirements of ANSI/TIA-568-C.2 Category 6A and ISO 11801 Class EA standards at swept frequencies 1 to 500 MHz, Meets ANSI/TIA-1096-A; Meets IEC 60603-7, Supports IEEE 802.3af, 802.3at, and IEEE 802.3bt type 3 and 4 for PoE applications up to 100 W, UL 1863 approved and RoHS Compliant
Maximum Operating Temperature (°C)	65
Maximum Operating Temperature (°F)	149
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	-14
Overall Length (In.)	1.17
Overall Length (mm)	29.7

**Packaging Detail**

UPC	07498303707
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.1619
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	1.6189