SEN-K643200H8

























NVR 64 In, H.265, max 8MP, 320Mbps, no POE, I/O, 2xHDMI 4K, VGA, 2x Ethernet, Rack, Fisheye&Raid Function.

- Operating System Linux Embedded
- H.264/H.265 compression modes
- Pentaplex: preview, record, playback, backup and remote access
- Smart Phone support Android, iPhone and iPad
- ONVIF protocol support
- 4K video display on main HDMI
- Free DDNS service

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, form retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEN-K643200H8



Technical Specifications	
Operating System	Embedded Linux
Multiplex Function	Pentaplex
Basic Internal Storage	0 GB
Max. Storage Capacity	8 Hard Disk (3.5 inch SATA), 8 TB, 2 x eSATA port
Support of RAID	Raid 0/1/5/6/10
Video Inputs	64 IP cameras
Recording Bandwidth	max. 320 Mbps
HDMI/VGA output	Up to 12 Megapixel
Video Compression	H.264, H.265
Video Streaming	2 independent Video-Streams
Video Outputs	1x VGA, 2x HDMI
Display resolution	Up to 4K on HDMI, VGA: 1920x1080, 1280x1024
Display Speed	Real-time
Audio Inputs	1 CH, RCA, 64 Channel via Network
Audio Outputs	1 CH, RCA
Recording Mode	Manual, Schedule, Motion, Alarm
Fisheye settings	Wall, Ground and Ceiling Installation, 360°, Panoramic View, 2x180°, 4 Windows
Alarm Inputs	8, Support IPC alarm input
Alarm Outputs	4, Support IPC alarm output
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Motion detection, Alarm Input, System Exceptions, Video Loss, Manual Trigger, Intelligent video analytics
Alarm Notification	Email / FTP, Pop-up video, Preset on PTZ, Relay, Snapshot Record, Video Record
Interfaces	1 x USB 3.0, 2 x USB 2.0
Network Interface	2x 10/100/1000Mbps
Network Protocol	DHCP, TCP/IP, PPPoE, SMTP, NTP, UPnP, DNS, DDNS, HTTP, HTTPS, RTSP, FTP, ONVIF, AutoDDNS, AutoNAT, QRCode
Monitoring	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Androïd)
Max. Users	20
Playback	Synchronised playback of max. 16 cameras
Search Mode	Time, Motion, Alarm, Timeline
Smart Search Function	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events

SEN-K643200H8



Technical Specifications	
External Backup	USB HDD, USB Memory, Network
Supply Voltage	100 ~ 240 VAC, 50/60Hz
ONVIF compliant	Yes
Operating Temperature	-10°C ~ +50°C
Operating Humidity	10% ~ 90%, non-condensing
Dimensions (W x H x D)	430 x 89 x 453 mm - 16.93 x 3.5 x 17.83 ln
Power Consumption (W)	15
Weight	5 kg - 11.02 lbs