

SER-7E0820TEF

DVR 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 8 In 4K 6fps, 4K Lite\5MP\4MP 12fps, 5MPLite 20fps, 4MPLite\1080p\720p 25fps più 8 IP 4K/20fps, HDMI(4K)/VGA/SPOT, Audio

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Possibility to change the analog input into IP input
- 4K video display on main HDMI
- Real-Time Recording @ 1080p
- Operating System - Linux Embedded
- Pentaplex: preview, record, playback, backup and remote access
- Free DDNS service
- Support up to 8MP Resolution Recording

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SER-7E0820TEF

Technical Specifications

Operating System	Embedded Linux
Basic Internal Storage	0 GB
Max. Storage Capacity	2 Hard disk (3.5 inch SATA), up to 8TB
External Backup	USB Memory, Network
Video Inputs	8 CH 960H/HD-TVI/AHD/HD-CVI (BNC) + 8 CH IP, up to 16ch IP
Video Outputs	1x VGA, 1x BNC (spot out), 1x HDMI
Display resolution	Up to 4K on HDMI, Up to 1920x1080 (HDMI / VGA)
Video Compression	H.264, H.265, Single/ Dual Stream for each channel
Display Speed	Real-time
Recording Mode	Continuous, Event Alarm, Motion, Schedule
HDMI/VGA output	4K, 4KLite, 5MP e 5MPLite (solo TVI-AHD), 4MP, 4MPLite, 1080P, 720P, 960H
Recording Speed	4K 6fps, 4KLite\5MP\4MP 12fps, 5MPLite 20fps, 4MPLite\1080p\720p 25fps
Alarm Inputs	8
Alarm Outputs	2
Audio Inputs	8 CH, RCA
Audio Outputs	1 CH, RCA
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Motion detection, Alarm Input, Video Loss, System Exceptions
Alarm Notification	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
Interfaces	RS-485, 1 x USB 2.0, 1 x USB 3.0
Serial Protocol	Pelco D, Pelco P, ...
Network Interface	1x 10/100/1000 Base T/TX (RJ-45)
Bandwidth	Incoming 32Mbps, Outgoing 96Mbps
Network Protocol	DHCP, TCP/IP, HTTP, SMTP, NTP, DNS, PPPoE, DDNS, ONVIF, AutoNAT, AutoDDNS, QRCode
Monitoring	Web viewer, CMS (Microsoft Windows & Apple iOS), Smartphone viewer (iPhone, Android)
Max. Users	10
Playback	Synchronised playback of max. 8 cameras
Search Mode	Date/Time, Event Alarm, Motion, Video Loss
Supply Voltage	12 Vdc (230 Vac power adaptor included)

SER-7E0820TEF**Technical Specifications**

Operating Temperature	-10°C ~ +50°C
Humidity	10 ~ 90%RH
Dimensions (W x H x D)	380 x 45 x 268 mm - 14.96 x 1.77 x 10.55 In
Power Consumption (W)	15
Weight	3.1 kg - 6.83 lbs