

SEI-T42210TI-LPR



Bullet IP, 2Mpxl, 7-22mm MOTOR., STARLIGHT, ICR, WDR 120dB, LEDs 70-100mt, IP67/IK10, POE, H.265, LPR

- High Performance for 2 Mega Pixel / Full HD Resolution
- H265 for high compression rate and stable stream control
- Embedded with LPR algorithm inside the camera
- Triple-streaming support
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-T42210TI-LPR

Technical Specifications

Image Sensor	1/2,8" Starlight Progressive Scan CMOS
Pixels - Total	1920(H) x 1080(V)
Video Resolution	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.005 lux @ F1.6
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	7~22 mm
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	70-100 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+, Triple Streaming
ONVIF compliant	Profile S
License plate recognition	License Plate recognition up to 70km/h
LPR Features	White-List & Black-List on camera (1000 Plates), Overview and cutout of plate for picture
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 CH, Line in
Audio Outputs	1 CH, RCA
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)

Technical Specifications

Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions (W x H x D)	279.5 x 100.3 x 88.9 mm - 11 x 3.95 x 3.5 In
Power Consumption (W)	11
Weight	1.06 kg - 2.34 lbs