

## BS132N Battery 12 V 45 Ah



## **Details**

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

## BS132N Battery 12 V 45 Ah

## **Technical specifications**

General	
Product type	Sealed lead acid battery
Electrical characte	ristics
Nominal voltage	12 V
Nominal capacity	45 Ah
Internal approx.	5 mOhm
resistance	
Charge / discharge	1
Max. charge voltage	13.8 VDC at +20°C
Max. charge current	13.5 A
Max. discharge current	225 A
Temperature	
Charging temperature	0 to +40°C
Discharging temperatur	e-15 to +50°C
Physical	
Physical dimensions	198 x 166 x 171 mm
Net weight	14 kg
Material	ABS
Terminal type	MS bolt & nuts
Environmental	
Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C
Regulatory	
Compliancy	CE, RoHS 2, WEEE
Certification	VdS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.