

SEI-T6227TI


Bullet IP, 3Mpxl, 2.8-12mm, STARLIGHT, ICR, dWDR, LEDs 30-50mt, IP66, PoE, H265

- STARLIGHT technology for extreme brilliant images in low light conditions
- H265 for high compression rate and stable stream control
- Triple-streaming support
- ONVIF protocol support
- Power-over-Ethernet support
- IP66, IK10
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-T6227TI

Technical Specifications

Image Sensor	1/2.8" CMOS Sony Exmor™ Progressive Scan
Pixels - Total	2048 (H) x 1536 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.01 lux @ F1.2
Sensitivity B/W	0 Lux LED IR on, 0.001 lux @ F1.2
Lens Focal Length	2.8 ~ 12 mm
Horizontal Viewing Angle	78,5° (Wide) ~ 30° (Tele)
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	2DNR/3DNR (Off/On)
Video Resolution	1280x720 (25 fps), 1920x1080, 2048x1536 (25fps), 720x576
Video Compression	H.264, H.265, MJPEG, Triple Streaming
ONVIF compliant	Profile S
Max. Users	10
SD memory	supports up to 64 GB capacity of micro TF Card
Intelligent Video Analytics	Tampering, Virtual Line, Appear / Disappear, Area Entrance
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 OUT MIC
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser

Technical Specifications

Operating Temperature	-20°C ~ +50°C
Humidity	10 ~ 90%RH
Power Consumption (W)	5
Weight	1.093 kg - 2.41 lbs
Dimensions	∅ 109 x 284 mm - 4.29 x 11.18 In