

IO950ND

Apollo IO Unit - DIN Rail Mount (SA4700-302)

General

IO950ND is the new DIN-Rail input/output unit which provides supervision of one or more normally open contacts connected to a single pair of cables and a set of changeover relay output contacts.

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Dettagli

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more NO switches on a single cable pair
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO950ND

Apollo IO Unit - DIN Rail Mount (SA4700-302)

Specifiche tecniche

Elettrico

Operating voltage	17 to 35 VDC
-------------------	--------------

Fisico

Dimensioni fisiche	102 x 33 x 33 mm
--------------------	------------------

Peso netto	49 g
------------	------

Ambientale

Temperatura operativa	-40 to +70°C
-----------------------	--------------

Umidità relativa	0 to 95% noncondensing
------------------	------------------------

Environment	Interno
-------------	---------

Regolatorio

Certificazioni	CPR, EN54-17, EN54-18
----------------	-----------------------

Electrical

Protocol voltage	5-13V peak to peak
------------------	--------------------

Current consumption

Power-up surge	0.9 mA
----------------	--------

Quiescent	0.5 mA
-----------	--------

LEDs disabled (max.)	0.5 mA
----------------------	--------

Alarm (LEDs On) (max.)	3.5 mA
------------------------	--------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 4 May 2023 - 17:07