SEI-P16140-TI-360













Panoramic 360° IP, 8x2MP=16MP ICR, dWDR 120dB, STARLIGHT, LEDs 20mt, IP66/IK10, POE, H.265, Advanced VCA A.

- 16 Megapixel IP Panoramic Camera with real time video streaming
- 1/2.8" CMOS 2Megapixel x 8(16MP)
- · H265 for high compression rate and stable stream control
- · Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- · ONVIF protocol support
- Power-over-Ethernet support
- IP66, IK10

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, form retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-P16140-TI-360



Technical Specifications	
-	4/0.0 D
Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	8192 (H) x 1800 (V)
Video Resolution	Main Stream 8192x1800, Sub stream 2048x896, third stream 704x320
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.008Lux@F2.0
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	3.3mm, x8
Shutter Speed	1 ~ 1/100,000 sec
Max. IR Distance	20 m
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+
ONVIF compliant	Profile S
Advanced Video Analytics	Advaced video Analitycs A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crow detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens Unattended Baggage, Area Entrance, Virtual fence
Max. Users	15
SD memory	up to 256 GB
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 CH, Line out
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	24 Vac / 24 Vdc ±10%, PoE++ (IEEE 802.3bt calss 6)

SEI-P16140-TI-360



Technical Specifications	
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30°C ~ +55°C
Humidity	less than 95%, non condensing
Power Consumption (W)	25
Weight	3.26 kg - 7.19 lbs
Dimensions	Ø 273 mm - 10.75 ln