

BS129N

Battery 12 V, 26 Ah

Product overview

Sealed Lead Acid battery 12 V / 26 Ah with MS bolt & nuts terminal type.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS129N

Battery 12 V, 26 Ah

Technical specifications

General

Product type	Sealed lead acid battery
--------------	--------------------------

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	26 Ah
Internal approx. resistance	10 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	7.8 A
Max. discharge current	130 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	166 x 175 x 125 mm
Net weight	9.528 kg
Shipping weight	9.528 kg
Colour	Dark grey
Material	ABS
Terminal type	MS bolt & nuts

Environmental

Fire retardant	No
Vandal proof	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:28