

## SEI-E4225TI-H


**Eyeball IP, FullHD, 2.8-12mm, ICR, dWDR, LEDs 30-50mt, IP67,IK10, PoE, STARLIGHT**

- 2 Megapixel Sony Starvis STARLIGHT Progressive Scan
- Varifocal Lens:  $f = 2.8 - 12$  mm
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator
- IP 67 Certification
- IK10

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2,8" CMOS Progressive Scan Sony Starvis Starlight IMX307
<b>Pixels - Total</b>	1920(H) x 1080(V)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.005 lux @ F1.6
<b>Lens Focal Length</b>	2.8 ~ 12 mm
<b>Iris F-Number</b>	F= 1.4
<b>Horizontal Viewing Angle</b>	95.4° -35.5°
<b>S/N Ratio</b>	>50 dB
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	30/50 m (according to scene reflexion)
<b>WDR</b>	D-WDR (Digital wide dynamic range)
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	H.264, MJPEG, H.265
<b>Video Resolution</b>	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps)
<b>ONVIF compliant</b>	Profile S
<b>Micro SDHC memory:</b>	microsd card slot up to 128GB
<b>Max. Users</b>	3
<b>Motion Detection</b>	Yes
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	SMTP, UPnP, HTTPS, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30°C ~ +60°C
<b>Humidity</b>	10 ~ 90%RH
<b>Supply Voltage</b>	12 Vdc, PoE (IEEE 802.3af)
<b>Power Consumption (W)</b>	9.5
<b>Weight</b>	0.687 kg - 1.51 lbs
<b>Dimensions</b>	Ø 111.5 mm - 4.39 In