


SEI-P6321TIO



MiniPTZ Dome Camera IP, 4MP, Starlight, 4x Zoom, IR LEDs 50mt, ICR, WDRi, IP66, H.265, Autotracking, 12VDC POE+, NDAA.

- 4MP Resolution
- STARLIGHT technology for extreme brilliant images in low light conditions
- 4x motorized optical zoom
- Integrated IR LEDs 50mt range
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Colour/B&W function with removable IR cut filter
- Operating Temperature (-30°C~ 60°C)
- TVS 6KV lightning protection, surge protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-P6321TIO



Technical Specifications

Image Sensor	1/2.7" progressive scan CMOS
Scanning System	Progressive
Video Resolution	4MP 2560 (H) x1440 (V)
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity B/W	0 Lux LED IR on, 0.002 lux @ F1.6
Sensitivity Colour	0.1 lux @ F1.6
Lens Focal Length	2.8 ~ 12 mm
Optical Zoom Ratio	4x
Lens Drive Type	Auto Iris (DC)
Max. IR Distance	50 m
Alarm Inputs	1
Alarm Outputs	1
S/N Ratio	>50 dB
White Balance	Auto / Manual
WDR	True WDR
DNR	Yes
Network Protocol	DHCP, TCP/IP, UPnP, PPPoE, HTTPS, SMTP, NTP, DNS, DDNS, HTTP, SNMP, IPv4/IPv6, RTP, UDP, QoS, RTSP, FTP, IGMP, ONVIF, ICMP, RTCP, AutoDDNS
Video Compression	H.264, MJPEG, H.265, H.264+, H.265+
Streaming	Triple Streaming
Alarm Notification	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
Advanced Video Analytics	Advanced video Analytics B: Area intrusion\line crossingwith Object Classification (Human, Vehicle, Bike), Area intrusion, line crossing, images change., Face detection, Face capture, Autotracking
Network Interface	10/100 Base-T
Web Browser	All major browsers are supported
PTZ Control	3D Intelligent Position
Pan Speed	Max. 80°/s
Tilt Speed	max. 60°/s
Range Panning	355° limited Rotation
Number of Preset	300
Number of Pattern	8
Privacy zones	N.D
Home position	Preset/Sequence/Auto Pan/Cruise

SEI-P6321TIO



Technical Specifications

OSD	Yes
Auto Flip	N.D.
Protection Rating	IP66
Surge protection maximum voltage	Transient voltage 6000V
Operating Temperature	-40°C ~ +65°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, Power adaptor included, 802.3at PoE+
Accessories included	Bracket & PSU included
Power Consumption (W)	20.2
Weight	1.2 kg - 2.65 lbs
Dimensions	Ø 130 mm - 5.12 In