



NetKey® Patch Cord

NK6PC4MY

Netkey copper patch cord, category 6, 4 meters, off white UTP cable.

Specifications

Application	1) Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), and 1000BASE-T (Gigabit Ethernet) 2) 155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM 3) Token Ring 4/16 4) Voice over internet protocol (VoIP)
Product Type	Patch Cord
Conductor Gauge (AWG)	24
Conductor Gauge (kcmil)	0.4
Sub Brand	NetKey®
Performance Level	Category 6
Conductor Type	Stranded
Cable Construction	U/UTP
Patch Cord Type	Unshielded
Connector 1 Type	Modular Plug
Connector 2 Type	Modular Plug
Overall Length (m)	4
Nominal Cable Outside Diameter (mm)	6
Wiring Scheme	T568B
Maximum Operating Temperature (°C)	60
Minimum Operating Temperature (°C)	-10
Maximum Storage Temperature (°C)	70
Boot Color	Clear
Color	Off White
Flammability Rating	CM
Standards Met	Exceeds ANSI/TIA-568.2-D Category 6 and ISO 11801 Class E channel requirements at swept frequencies up to 250 MHz; Meets ANSI/TIA-568.2-D and ISO 11801 Category 6 component requirements at swept frequencies up to 250 MHz; Complies with ANSI/TIA-1096-A; Meets IEC 60603-7; Supports IEEE 802.3af/802.3at and 802.3bt type 3 and type 4 PoE applications; cULus Listed; UL 1863 and CAN/CSA-C22.2 (UL File E129886); RoHS Compliant
IEC Variant	60603-7
PoE Compatibility	PoE, PoE+, PoE++

Specifications (continued)

Plug Type	8 Position
RapidID™ Enabled	No
Part Features	100% performance tested, Patented tangle free latch, Slender strain relief boot, Identification and Variety of color and lengths available

Packaging Detail

UPC	07498378580
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0347
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.3474