

**SER-6E3280TEF**

**DVR 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 32 In RealTime@1080p o 12fps@4MP (AHD) o 10fps@5MP plus 4 IP 4MP/25fps/6Mbps, HDMI(4K)/HDMI(2K)/VGA/SPOT, Audio, Rack**

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Support up to 5MP Resolution Recording
- H.264 compression modes
- 4K video display on main HDMI
- Real-Time Recording @ 1080p
- Operating System - Linux Embedded
- Pentaplex: preview, record, playback, backup and remote access
- Free DDNS service

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SER-6E3280TEF



### Technical Specifications

<b>Operating System</b>	Embedded Linux
<b>Basic Internal Storage</b>	0 GB
<b>Max. Storage Capacity</b>	8 Hard Disk (3.5 inch SATA), up to 8TB
<b>External Backup</b>	USB Memory, Network
<b>Video Inputs</b>	32 CH 960H/HD-TVI/AHD/HD-CVI (BNC) + 4 CH IP
<b>Video Outputs</b>	1x VGA, 1x BNC (spot out), 2x HDMI
<b>Display resolution</b>	Up to 4K on HDMI, Up to 1920x1080 (HDMI / VGA)
<b>Video Compression</b>	Single/ Dual Stream, H.264 High Profile
<b>Display Speed</b>	Real-time
<b>Recording Mode</b>	Continuous, Event Alarm, Motion, Schedule
<b>HDMI/VGA output</b>	Up to 5 Megapixel, FullHD (1920x1080), HD (1280x720), 960H (960x576)
<b>Recording Speed</b>	RealTime@1080p/720p/960H + 32Mbps total on 4 IP channels (max 4Mpxl), 12 fps @ 4 Megapixel (per channel) AHD
<b>Audio Inputs</b>	16 CH, RCA
<b>Audio Outputs</b>	1 CH, RCA
<b>Alarm Inputs</b>	16
<b>Alarm Outputs</b>	4
<b>Motion Detection</b>	On/ Off/ Area Setting
<b>Alarm Trigger</b>	Motion detection, Alarm Input, Video Loss, System Exceptions
<b>Alarm Notification</b>	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
<b>Interfaces</b>	RS-485, 2 x USB 2.0, 1 x USB 3.0
<b>Serial Protocol</b>	Pelco D, Pelco P, ...
<b>Network Interface</b>	1x 10/100/1000 Base T/TX (RJ-45)
<b>Network Protocol</b>	DHCP, TCP/IP, HTTP, SMTP, NTP, DNS, PPPoE, DDNS, ONVIF, AutoNAT, AutoDDNS, QRCode
<b>Monitoring</b>	Web viewer, CMS (Microsoft Windows & Apple iOS), Smartphone viewer (iPhone, Android)
<b>Max. Users</b>	10
<b>Playback</b>	Synchronised playback of max. 16 cameras
<b>Search Mode</b>	Date/Time, Event Alarm, Motion, Video Loss
<b>Supply Voltage</b>	12 Vdc (230 Vac power adaptor included)
<b>Operating Temperature</b>	-10°C ~ +50°C
<b>Humidity</b>	10 ~ 90%RH
<b>Dimensions ( W x H x D)</b>	430.02 x 100 x 453 mm - 16.93 x 3.94 x 17.83 In
<b>Power Consumption (W)</b>	15
<b>Weight</b>	3.1 kg - 6.83 lbs