

DC428

Contatto magnetico installazione a pavimento, con cavo, alta sicurezza, certificato EN Grado 4. Grigio

The magnetic detector DC428 which is certified according to the requirements of EN 50131-2-6 grade 4 and VdS Class C, allows for contact-free opening monitoring of doors and windows in accordance with the highest security requirement specifications.

Compared to other high-security magnetic detectors, this product also has enhanced external field monitoring, which can be used to detect an abnormally large difference between the code that was applied and the code that was taught in.

The ability to teach-in this detector to one of eight different magnet variants at the installation location provides for a higher level of security and allows the system to remain relatively flexible with respect to tolerances. The code is assigned at the installation location and is not already defined for the detector at the factory. If a magnetic component is lost or damaged, you can simply replace it with a new one and then teach-in the detector to the new component.

According to the EN the connection wires are suitable for the connection of an alarm wire loop. The maximum number of detectors that can be connected in series for the evaluation is based on the maximum permitted values of the relevant alarm system.

The electronic switches, are potential-free relating to direct current from the rest of the circuit, and are closed when not in use.



Dettagli

- Certified to the highest possible security standard for magnetic switches
- High dust and humidity resistance (IP67)
- Enhanced external field monitoring
- Ability to teach-in to one of eight different magnet variants
- LED providing feedback for installer during entire teach-in process
- Protection against removal of the sensor from the installation surface

DC428

Contatto magnetico installazione a pavimento, con cavo, alta sicurezza, certificato EN Grado 4. Grigio

Specifiche tecniche

Generale

Tipo di applicazione	Overhead
Tipo contatto	Electronic switch
Connettività	LIYY 9 x 0.14 mm ² copper tin-plated

Cablato / senza fili

Wired-wireless	Cablato
Operating gap	10-20 mm

Elettrico

Consumo di energia	monitoring mode : 5mA, learn-in mode LED : max 13mA
Voltage	12 to 24 VDC

Fisico

Dimensions magnet	121.5 x 45 x 25 mm
Dimensions contact / sensor	140 x 62 x 28 mm

Ambientale

Operating temperature	-40°C to +70°C
-----------------------	----------------

Regolatorio

Grado EN50131	Grado 4
---------------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:36