

## SEI-T6327TI



**Bullet IP, 4Mpxl, 2.8-12mm MOTOR., ICR, WDR 120dB, LEDs 50-70mt, IP67/IK10, POE, H.265, Face Detection, ADVANCED VCA A**

- 4 Megapixel IP Camera with real time video streaming
- 1/2.7" 2Megapixel CMOS
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

Image Sensor	1/3" CMOS (WDR)
Pixels - Total	2592 (H) x 1520 (V)
Video Resolution	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288) , 4MP (2592x1520)
Scanning System	Progressive
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity Colour	0.05 Lux@F1.6
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	2.8 ~ 12 mm Motorized @F1.4
Iris Operation	Auto iris (DC)
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+, Triple Streaming
ONVIF compliant	Profile S
Advanced Video Analytics	Advanced video Analytics A: Area intrusion/line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 CH, Line in
Audio Outputs	1 CH, RCA, None
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)

**Technical Specifications**

<b>Interfaces</b>	RS-485
<b>Supply Voltage</b>	12 Vdc / PoE (IEEE 802.3af)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30° C ~ +60° C
<b>Humidity</b>	less than 95%, non condensing
<b>Dimensions ( W x H x D)</b>	279.5 x 100.3 x 88.9 mm - 11 x 3.95 x 3.5 In
<b>Power Consumption (W)</b>	10
<b>Weight</b>	1.04 kg - 2.29 lbs