

SER-6E3280TEF2

DVR 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 32 In RealTime@1080p o 12fps@4MP\5MP o 8fps@8MP plus 32 IP 8MP/25fps/6Mbps, HDMI(4K)/HDMI2(1080p)/VGA/SPOT, Audio, Rack,RAID.

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Support up to 8MP Resolution Recording
- 4K video display on main HDMI
- H265 for high compression rate and stable stream control
- Real-Time Recording @ 1080p
- Operating System - Linux Embedded
- Pentaplex: preview, record, playback, backup and remote access
- Free DDNS service

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SER-6E3280TEF2

Technical Specifications

Operating System	Embedded Linux
Basic Internal Storage	0 GB
Max. Storage Capacity	8 Hard Disk (3.5 inch SATA), up to 8TB
External Backup	USB Memory, Network
Video Inputs	32 CH 960H/HD-TVI/AHD/HD-CVI (BNC) + 32 CH IP (up to 64)
Video Outputs	1x VGA, 1x BNC (spot out), 2x HDMI
Display resolution	Up to 4K on HDMI, Up to 1920x1080 (HDMI / VGA)
Video Compression	H.265, Single/ Dual Stream for each channel, H.264 High Profile
Display Speed	Real-time
Recording Mode	Continuous, Event Alarm, Motion, Schedule
HDMI/VGA output	Up to 8 Megapixel
Recording Speed	12fps@8MPLite
Audio Inputs	16 CH, RCA
Audio Outputs	1 CH, RCA
Alarm Inputs	16
Alarm Outputs	8 Relay
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Motion detection, Alarm Input, Video Loss, System Exceptions
Alarm Notification	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
Interfaces	RS-485, 2 x USB 2.0, 1 x USB 3.0
Serial Protocol	Pelco D, Pelco P, ...
Network Interface	1x 10/100/1000 Base T/TX (RJ-45)
Network Protocol	DHCP, TCP/IP, HTTP, SMTP, NTP, DNS, PPPoE, DDNS, ONVIF, AutoNAT, AutoDDNS, QRCode
Monitoring	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
Max. Users	10
Playback	Synchronised playback of max. 16 cameras
Search Mode	Date/Time, Event Alarm, Motion, Video Loss
Supply Voltage	230 Vac
Operating Temperature	-10°C ~ +50°C
Humidity	10 ~ 90%RH
Dimensions (W x H x D)	445 x 90 x 436 mm - 17.52 x 3.54 x 17.17 In
Power Consumption (W)	70
Weight	3.1 kg - 6.83 lbs