

## SEI-V4223TI


**Minidome IP AV, 2MP, 2.8-12mm, ICR, WDR 120db, LEDs 20-30mt, IP66, PoE, VCA Basic**

- 2 Megapixel IP Camera with Full HD 1080P real time video
- Triple-streaming support
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator
- IP66, IK10

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SEI-V4223TI

### Technical Specifications

Image Sensor	1/2.7" Progressive scan CMOS 2 Megapixel
Pixels - Total	1920(H) x 1080(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.05 lux f1.2
Lens Focal Length	2.8 ~ 12 mm
S/N Ratio	>50 dB
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, Triple Streaming
Video Resolution	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps), 2048x1536 (25 fps)
ONVIF compliant	Profile S
Max. Users	4
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-20°C ~ +50°C
Humidity	10 ~ 90%RH
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	5
Weight	1025 kg - 2259.74 lbs
Dimensions	Ø 150 mm - 5.91 In