

GS300

Sensore piezo rottura vetri mini con memoria.

High Performance

The glassbreak detector GS300 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS300 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard (exists also in 6 & 20 meters). They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



Dettagli

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

GS300

Sensore piezo rottura vetri mini con memoria.

Specifiche tecniche

Generale

Technology	Piezo
Tipo di vetro	Lastra
Range	2 m radius
Tamper switch	No

Cablato / senza fili

Wired-wireless	Cablato
----------------	---------

Elettrico

Power supply value	3 to 16 VDC
Current consumption	4 mA @ 6 VDC 9 mA @ 12 VDC

Fisico

Physical dimensions	37 x 19 x 12 mm
Peso netto	50 g
Colour	Bianco
Tipo di montaggio	Montaggio a superficie

Ambientale

Temperatura operativa	-25 to +70°C
IP rating	IP67

Regolatorio

Certification	EN50131 Grade 2, VdS
---------------	----------------------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:33