

## SEI-T6329TI



**Bullet IP, 4Mpxl, 2.8-12mm MOTOR., ICR, WDR 120dB, LEDs 50-70mt, IP67/IK10, POE, H.265, Face Detection, ADVANCED VCA A-VCA2.0, NDAA.**

- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Built-in SD card reader for message recording in case of no answer
- Block of access after multiple login failed tentatives
- System Log preserved after system reset
- Request to modify password at first login
- AES128 encrytion on local SD recording

## SEI-T6329TI



### Summary

---

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

Image Sensor	1/3" CMOS (WDR)
Pixels - Total	2592 (H) x 1520 (V)
Video Resolution	4MP/2K/3MP/1080P / 720P (60Hz: 1~ 30fps; 50Hz: 1~25fps )
Scanning System	Progressive
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity Colour	0.05 Lux@F1.6
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	2.8 ~ 12 mm Motorized @F1.4
Iris Operation	Auto iris (DC)
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+, Triple Streaming
ONVIF compliant	Profile S, Profile G
Advanced VCA2.0-Metadata	Cattura simultaneamente il corpo umano, il veicolo a motore e il veicolo non a motore ed estrae 13 caratteristiche umane, 5 caratteristiche del veicolo a motore e 1 caratteristica del veicolo non a motore
Advanced Video Analytics	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Motion Detection, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
VCA Distance	Human: 8m (2.8mm) ~ 25m (12mm), Vehicle: 15 m (2.8mm) ~ 35m (12mm)
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 CH, Line in

## SEI-T6329TI



## Technical Specifications

Audio Outputs	1 CH, RCA, None
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions ( W x H x D)	279.5 x 100.3 x 88.9 mm - 11 x 3.95 x 3.5 In
Power Consumption (W)	10
Weight	1.04 kg - 2.29 lbs