

SEI-E4322TI-H


Eyeball IP, FullHD, 2.8-12mm Motor, ICR, dWDR, LEDs 30-50mt, IP67,IK10, PoE, STARLIGHT

- STARLIGHT technology for extreme brilliant images in low light conditions
- Varifocal Lens: $f = 2.8 - 12 \text{ mm}$
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator
- IP 67 Certification
- IK10

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2,8" Starlight Progressive Scan CMOS
Pixels - Total	1920(H) x 1080(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.0028 lux @ F1.2
Lens Focal Length	2.8 ~ 12 mm Motorized
Iris F-Number	F= 1.4
Horizontal Viewing Angle	91° (Wide) ~ 37.5° (Tele)
S/N Ratio	>50 dB
Shutter Speed	1 ~ 1/100,000 sec
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, Single/ Dual Stream for each channel
Video Resolution	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps)
ONVIF compliant	Profile S
Micro SDHC memory:	microsd card slot up to 128GB
Max. Users	3
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	SMTP, UPnP, HTTPS, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30°C ~ +60°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	9
Weight	0.66 kg - 1.46 lbs
Dimensions	Ø 111.5 mm - 4.39 In