



Eyeball IP, 5Mpxl, 3.3-12mm Motorizzata, ICR, WDR 120dB, LEDs 30-50mt, IP67, IK10, Po, VCA Basic.

- 5 Megapixel resolution
- Motorized varifocal lens for easy remote focusing
- Triple-streaming support
- H265 for high compression rate and stable stream control
- ONVIF protocol support
- Power-over-Ethernet support
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-E7320TI

Technical Specifications

Image Sensor	1/2.5" Progressive Scan CMOS 5MP Aptina AR0521
Pixels - Total	2560 (H) x 1440 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.013 lux @ F1.2
Lens Focal Length	3.3 ~ 12 mm, Motorized
Horizontal Viewing Angle	93.9° (Wide) ~ 34.8° (Tele)
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
Video Resolution	1920x1080 (1080p), 1280x720 (720p), 4MP 2560 (H) x1440 (V), 3MP 2304 (H) x1296 (V)
ONVIF compliant	Profile S
Max. Users	10
Audio Inputs	1 in Mic
Audio Compression	G.711A
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	9.5
Weight	0.67 kg - 1.48 lbs
Dimensions	Ø 111.5 mm - 4.39 In