

## SEN-G32801H2-A1


**NVR 32 In, H.265, max 8MP, 256Mbps, no POE, HDMI 4K, Fisheye, Face Recognition, Rack.**

- Operating System - Linux Embedded
- H.264/H.265 compression modes
- Support up to 8MP Resolution Recording
- Pentaplex: preview, record, playback, backup and remote access
- Smart Phone support Android, iPhone and iPad
- ONVIF protocol support
- 4K video display on main HDMI
- Free DDNS service

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Operating System</b>	Embedded Linux
<b>Multiplex Function</b>	Pentaplex
<b>Basic Internal Storage</b>	0 GB
<b>Max. Storage Capacity</b>	2 Hard disk (3.5 inch SATA), up to 8TB
<b>Video Inputs</b>	32 IP cameras
<b>Recording Bandwidth</b>	max. 256 Mbps
<b>HDMI/VGA output</b>	Up to 8 Megapixel
<b>Video Compression</b>	H.264, H.265
<b>Video Streaming</b>	2 independent Video-Streams
<b>Video Outputs</b>	1x HDMI, 1x VGA
<b>Display resolution</b>	Up to 4K on HDMI, VGA: 1920x1080, 1280x1024
<b>Display Speed</b>	Real-time
<b>Audio Inputs</b>	1 CH, RCA, 32 channels (over IP)
<b>Audio Outputs</b>	1 CH, RCA
<b>Recording Mode</b>	Manual, Schedule, Motion, Alarm
<b>Alarm Inputs</b>	None, Support IPC alarm input
<b>Alarm Outputs</b>	None, Support IPC alarm output
<b>Motion Detection</b>	On/ Off/ Area Setting
<b>Fisheye settings</b>	Wall, Ground and Ceiling Installation, 360°, Panoramic View, 2x180°, 4 Windows
<b>Intelligent Video Analytics</b>	Motion /Moved-Fixed Objects /Fence /Enter-Exit Area
<b>Face recognition</b>	Face Recognition
<b>Alarm Trigger</b>	Alarm Input, Manual Trigger, Motion detection, System Exceptions, Video Loss
<b>Alarm Notification</b>	Email / FTP, Pop-up video, Preset on PTZ, Snapshot Record, Video Record
<b>Interfaces</b>	1 x USB 2.0, 1 x USB 3.0
<b>Network Interface</b>	10/100/1000 Base-T
<b>Network Protocol</b>	AutoDDNS, AutoNAT, DDNS, DHCP, DNS, NTP, PPPoE, QRCode, SMTP, TCP/IP, UPnP
<b>Monitoring</b>	Web viewer, CMS (Microsoft Windows & Apple iOS), Smartphone viewer (iPhone, Android)
<b>Max. Users</b>	10
<b>Playback</b>	Synchronised playback of max. 16 cameras
<b>Search Mode</b>	Time, Motion, Alarm, Timeline
<b>Smart Search Function</b>	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events

**SEN-G32801H2-A1****Technical Specifications**

<b>External Backup</b>	USB HDD, USB Memory, Network
<b>Supply Voltage</b>	12VDC, Power adaptor included
<b>ONVIF compliant</b>	Yes
<b>Operating Temperature</b>	-10°C ~ +50°C
<b>Operating Humidity</b>	10% ~ 90%, non-condensing
<b>Dimensions ( W x H x D)</b>	380 x 52 x 268 mm - 14.96 x 2.05 x 10.55 In
<b>Power Consumption (W)</b>	15
<b>Weight</b>	5 kg - 11.02 lbs