

AS612

Self-activating outdoor siren with amber beacon - IMQ



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS612

Self-activating outdoor siren with amber beacon - IMQ

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	120 dB at 1 m (typical)

Flash specifications

Current consumption	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Operating voltage	13 to 14.2 V
Current consumption	600 mA 25 mA (standby current)

Physical

Physical dimensions	210 x 300 x 87 mm (W x H x D)
Net weight	2680 g
Material	Polycarbonate

Environmental

Operating temperature	-25 to 55 °C
IP rating	34



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:31