

SER-8D3280TEF



XVR Ibrido 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 32 Ingressi + 8 IP (sino a 24), 25fps@1080pLite/720p/960H o 12fps@1080p/4MPLite o 10fps@5MPLite più 8 IP 5MP/25fps/4Mbps, HDMI/VGA/SPOT, I/O, Rack, NDAA

- Real-Time Recording @ 720p, 12fps@1080p/4MPLite or 10fps@5MPLite for each channel
- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Operating System - Linux Embedded
- Pentaplex: preview, record, playback, backup and remote access
- Various recording features (Normal, schedule, motion, alarm)
- Free DDNS service
- H265 for high compression rate and stable stream control
- NDAA compliant

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SER-8D3280TEF



Technical Specifications

Operating System	Embedded Linux
Basic Internal Storage	0 GB
Max. Storage Capacity	4 Hard Disk (3.5 inch SATA), 1 x eSATA port, up to 10TB
External Backup	USB HDD, USB Memory, Network
Video Inputs	32 CH 960H/HD-TVI/AHD/HD-CVI (BNC) + 8 CH IP , up to 24ch IP
Video Outputs	1x VGA, 1x BNC (spot out), 1x HDMI
Display resolution	max. 1920 x 1080
Video Compression	H.265, Single/ Dual Stream for each channel
Recording Mode	Continuous, Event Alarm, Motion, Schedule
Recording Speed	5MPLite 10fps, 4MpLite\1080p 12fps, 1080Lite\720p\4CIF 25fps for channel
HDMI/VGA output	5MPLite (Only TVI-AHD), 4MPLite, 1080P, 720p
Audio Inputs	16 CH, RCA
Audio Outputs	1 CH, RCA
Alarm Inputs	16
Alarm Outputs	4
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Motion detection, Alarm Input, Video Loss, System Exceptions
Alarm Notification	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
Interfaces	RS-485, 1 x USB 2.0, 1 x USB 3.0
Serial Protocol	Pelco D, Pelco P, ..., CoC (control over coax)
Network Interface	1x 10/100/1000 Base T/TX (RJ-45)
Bandwidth	Incoming 40Mbps, Outgoing 160Mbps
Network Protocol	DHCP, TCP/IP, PPPoE, UPnP, SMTP, NTP, HTTPS, DNS, DDNS, HTTP, RTSP, ONVIF, AutoDDNS, AutoNAT, QRCode
Monitoring	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
Max. Users	15
Playback	Synchronised playback of max. 16 cameras
Search Mode	Date/Time, Event Alarm, Motion, Video Loss
Supply Voltage	220 ~ 240 VAC/50Hz
Operating Temperature	-10°C ~ +50°C
Humidity	10 ~ 90%RH
Dimensions (W x H x D)	440 x 70 x 390 mm - 17.32 x 2.76 x 15.35 In
Power Consumption (W)	30
Weight	9 kg - 19.84 lbs