

SEI-T7121TI



Bullet IP, 5Mpxl, 2.8mm, ICR, WDR(120dB), LEDs 20-30mt, IP67, IK10, PoE, VCA Basic, Face Detection.

- 5 Megapixel resolution
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-T7121TI

Technical Specifications

Image Sensor	1/2.5" Progressive Scan CMOS 5MP Aptina AR0521
Pixels - Total	2592 (H) x 1944 (V)
Video Resolution	3MP ?2048x1536), 1080p ?1920x1080?, 720p ?1280x720?, D1, CIF, 5M 2592x1944 (20fps), 4M 2592x1520 (30fps)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.013 lux @ F1.2
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	2.8 mm
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
ONVIF compliant	Profile S
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
Max. Users	10
SD memory	not support
Alarm	N/A
Audio Inputs	1 in Mic
Audio Outputs	None
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser

Technical Specifications

Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions (W x H x D)	74.5 x 74.5 x 167.7 mm - 2.93 x 2.93 x 6.6 In
Power Consumption (W)	7
Weight	0.67 kg - 1.48 lbs