

## SEI-P4521TIO


**PTZ Dome Camera IP, 2MP, Starlight, 25x Zoom, IR LEDs 150mt, ICR, WDR 120dB, IP66, H.265, Autotracking, 12VDC/POE+**

- 2 Megapixel PTZ IP Starlight Camera Real Time Streaming
- 25x optical zoom
- Integrated IR LEDs 150m range
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- High Speed Pan/Tilt (240°/sec Pan 160°/sec Tilt)
- Colour/B&W function with removable IR cut filter
- Operating Temperature (-30°C~ 60°C)
- TVS 6KV lightning protection, surge protection

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SEI-P4521TIO

### Technical Specifications

<b>Image Sensor</b>	1/2,8" Starlight Progressive Scan CMOS
<b>Scanning System</b>	Progressive
<b>Video Resolution</b>	1920x1080
<b>Col/B</b>	On/Off/Auto, IR-cut filter removable (ICR)
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.001 lux @ F1.6
<b>Sensitivity Colour</b>	0.005 lux @ F1.6
<b>Lens Focal Length</b>	4,8 ~ 120 mm
<b>Optical Zoom Ratio</b>	x 25
<b>Lens Drive Type</b>	Auto Iris (DC)
<b>Max. IR Distance</b>	150m
<b>Alarm Inputs</b>	None
<b>Alarm Outputs</b>	None
<b>S/N Ratio</b>	>50 dB
<b>White Balance</b>	Auto / Manual
<b>WDR</b>	120dB, True WDR
<b>DNR</b>	Yes
<b>Network Protocol</b>	DHCP, TCP/IP, PPPoE, UPnP, SMTP, NTP, HTTPS, DDNS, IPv4/IPv6, UDP, RTSP, FTP, QoS, ONVIF
<b>Video Compression</b>	H.264, MJPEG, H.265
<b>Streaming</b>	Triple Streaming
<b>Alarm Notification</b>	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
<b>Network Interface</b>	10/100 Base-T
<b>Web Browser</b>	All major browsers are supported
<b>PTZ Control</b>	3D Intelligent Position
<b>Pan Speed</b>	max. 240°/s
<b>Tilt Speed</b>	max. 160°/s
<b>Range Panning</b>	360° endless
<b>Number of Preset</b>	360
<b>Number of Pattern</b>	8
<b>Privacy zones</b>	N.D
<b>Home position</b>	Preset/Sequence/Auto Pan/Cruise
<b>Auto Flip</b>	Yes
<b>OSD</b>	Yes

## SEI-P4521TIO



## Technical Specifications

Protection Rating	IP66
Surge protection maximum voltage	Transient voltage 6000V
Operating Temperature	-40°C ~ +65°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE+ (IEEE 802.3at), Power adaptor included
Accessories included	Bracket & PSU included
Power Consumption (W)	22
Weight	2.1 kg - 4.63 lbs
Dimensions	Ø 173 mm - 6.81 In