

## SEI-T7221TI-PA



**Thermal Bullet IP 256x192 pxls and Visible 5MP, WDR 120dB, ICR, LEDs 20-30mt, Advanced VCA A, Temperature Detection, IP66, HFOV Thermal 56°, HFOV Visible 81°**

- 5 Megapixel resolution
- Advanced Analytics with car/human/bike classification
- Triple-streaming support
- Motorized varifocal lens for easy remote focusing
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2.7" progressive scan CMOS
<b>Pixels - Total</b>	2592 (H) x 1944 (V)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.008 lux @ (F1.4)
<b>Lens Focal Length</b>	2.8 ~ 12 mm, Motorized Autofocus
<b>Iris F-Number</b>	F= 1.4
<b>S/N Ratio</b>	>50 dB
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	30/50 m (according to scene reflexion)
<b>WDR</b>	WDR Pro 120dB
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	MJPEG, Triple Streaming, H.265+/H.265/H.264+/H.264
<b>Video Resolution</b>	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps), 2048x1536 (25 fps), 5M 2592x1944 (20fps), 4M 2592x1520 (30fps)
<b>Audio Inputs</b>	1
<b>Audio Outputs</b>	Built-in speaker, Speaker Used to activated audio alarm in case of VCA intrusion
<b>Alarm</b>	Input: 1 / Output: 1
<b>Advanced Video Analytics</b>	Advanced video Analytics B: Area intrusion\line crossingwith Object Classification (Human, Vehicle, Bike)
<b>ONVIF compliant</b>	Profile S
<b>Max. Users</b>	4
<b>Motion Detection</b>	Yes
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	UPnP, HTTPS, SNMP, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30° C ~ +60° C
<b>Humidity</b>	less than 95%, non condensing

**Technical Specifications**

<b>Supply Voltage</b>	12 Vdc, PoE (IEEE 802.3af)
<b>Dimensions ( W x H x D)</b>	80.5 x 80.5 x 217.7 mm - 3.17 x 3.17 x 8.57 In
<b>Power Consumption (W)</b>	11
<b>Weight</b>	0.65 kg - 1.43 lbs