

SEC-11E0541ITA


Eyeball 4in1, 8MPxIs, 2.8-12mm MOTOR., ICR, 20-30mt LEDs, OSD, 12VDC, IP66/IK10

- 1/2.5" 8Megapixel progressive scan CMOS
- 4-Hybrid Video Output HD-TVI/AHD/HD-CVI/960H
- CoC Control Over Coaxial Cable OSD Control
- IP66, IK10
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- Day/Night feature, switching through photocell
- Motorized varifocal lens for easy remote focusing

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEC-11E0541ITA

Technical Specifications

Image Sensor	1/2,5" 8MP Progressive Scan CMOS
Video Standard	AHD, HD-TVI, HD-CVI, CVBS (ITU-R-BT.470 PAL)
Video Resolution	5M 2592x1944 (20fps), 4M 2592x1520 (30fps), 3840x2160 @15fps
Horizontal Resolution	600TVL on analogue output
Col/B	Auto / Color / B&W, IR-cut filter removable (ICR)
Sensitivity B/W	0 Lux LED IR on, 0.01 lux @ F1.2
S/N Ratio	>52dB (AGC off)
Lens Focal Length	2.8 ~ 12 mm Motorized
ELC	Auto (1/50 ~ 1/100.000 sec.)
BLC Back Light	BLC / HLC / off
AGC	On/Off
Digital Noise Reduction	On/Off
De-Fog	not support
OSD	Yes, Multi Language with CoC (Control over Coaxial)
White Balance	ATW, Manual, AWC, Indoor, Outdoor
Max. IR Distance	20/30m (according to scene reflexion)
Optical Wavelength	850 nm
Smart IR	not support
Video Outputs	BNC (AHD / TVI / CVI / CVBS Selectable)
Mount	wall, Ceiling
Protection Rating	IP66, IK10
Operating Humidity	10% ~ 90%, non-condensing
Operating Temperature	-30°C ~ +50°C
Supply Voltage	12 VDC ±10%
Power Consumption (W)	5
Weight	0.66 kg - 1.46 lbs
Dimensions	∅ 130.3 x 110 mm - 5.13 x 4.33 In