

BEST SELLER



Shielded RJ45 Cat 6 TG Jack Module, Black

CJS688TGY

The Mini-Com® Cat 6 Shielded RJ45 TG Jack Module is designed to terminate 4-pair, 22-26 AWG twisted pair cable. Each module is 100% factory tested to exceed industry standard performance requirements. TG style termination eliminates the need for a termination tool. Each jack is individually serialized for traceability and is compatible with Mini-Com Shielded Modular Patch Panels and Faceplates. The jack module is black.

Specifications

Product Type	Jack Module
Performance Level	Category 6
Connector Type	Jack Module - Standard
Termination Style	TG Style
Body Material	Polycarbonate
Contact Material	Plated Phosphor Bronze
Module Type	Mini-Com®
Wiring Scheme	T568A/T568B
Shield Type	Shielded (STP)
Sub Brand	Pan-Net®
Maximum Operating Temperature (°C)	75
Maximum Operating Temperature (°F)	167
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	14
Maximum Storage Temperature (°C)	75
Maximum Storage Temperature (°F)	167
Minimum Storage Temperature (°C)	-40
Minimum Storage Temperature (°F)	-40
Resistance Properties	Heat-Resistant
Color	Black
Standards Met	Exceeds ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E Channel and Component Requirements at Swept Frequencies up to 250 MHz, Complies with ANSI/TIA-1096A, Meets IEC 60603-7 and IEC 60512-99-001, Rated for 2500 Cycles with IEEE 802.3af / 802.3at and Proposed 802.3bt Type 3 and Type 4 for up to 100W, UL 1863, UL 1863, UL 2043 and RoHS Compliant
Overall Depth (In.)	1.5
Overall Depth (mm)	38.1
Overall Height (In.)	0.74

Specifications (continued)

Overall Height (mm)	18.8
Overall Length (In.)	1.5
Overall Length (mm)	38.1
Overall Width (In.)	0.62
Overall Width (mm)	15.7

Packaging Detail

UPC	07498303563
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0032
Std. Ctn. Qty.	50
Std. Ctn. Volume (cf)	0.1605