

## SEI-T4125TI



**Bullet IP, 2Mpxl, 2.8mm, ICR, WDR(120dB), LEDs 20-30mt, IP67, IK10, PoE, VCA Basic.**

- 1/2.7" 2Megapixel CMOS
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SEI-T4125TI

### Technical Specifications

<b>Image Sensor</b>	1/2.7" Progressive Scan CMOS Aptina
<b>Pixels - Total</b>	1920(H) x 1080(V)
<b>Video Resolution</b>	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity Colour</b>	0.009 lux @ F1.2
<b>Sensitivity B/W</b>	0 Lux LED IR on
<b>Lens Focal Length</b>	2.8 mm
<b>Video Outputs</b>	1x CVBS (1Vpp), BNC
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	20/30m (according to scene reflexion)
<b>WDR</b>	WDR Pro 120dB
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	H.264, H.265, MJPEG, Triple Streaming
<b>ONVIF compliant</b>	Profile S
<b>Intelligent Video Analytics</b>	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
<b>Max. Users</b>	6 users at unicast mode
<b>SD memory</b>	not support
<b>Alarm</b>	N/A
<b>Audio Inputs</b>	1 in Mic
<b>Audio Outputs</b>	None
<b>Audio Compression</b>	G.711 a/u
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Interfaces</b>	RS-485
<b>Supply Voltage</b>	12 Vdc / PoE (IEEE 802.3af)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser

**Technical Specifications**

Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions ( W x H x D)	167.5 x 74.42 x 74.42 mm - 6.59 x 2.93 x 2.93 In
Power Consumption (W)	5
Weight	0.39 kg - 0.86 lbs