

3301 CG-S



Safety luminaire and escape sign luminaire



3301 CG-S with ceiling-recessed housing



Escape sign cube for 3301 CG-S



Ceiling tube

3301 CG-S

- Safety luminaire for recessed or surface ceiling mounting
- Easy mounting and relamping
- Optional with exit cube incl. 3 pictogram covers and a blind cover
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditures by STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

Viewing distance (mit RZ-Würfel)	20 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Housing material	Plastic
Weight incl. panel	2.26 kg
Housing colour	White
Type of mounting	Recessed and surface ceiling mounting
Connection terminals	Loop terminals 2 x 2.5 mm ²
Connection voltage	220 - 240 V, 50/60 Hz 176 V - 275 V DC
Current consumption - battery operation (220 V)	35 mA (TC-DEL 10 W) 50 mA (TC-DEL 13 W)
Power consumption mains operation	16 VA (TC-DEL 10 W) 23 VA (TC-DEL 13 W)
Permissible ambient temperature	-10 °C to +40 °C
Light source	10-13 W/TC-DEL

Ordering details

Type	Scope of supply	Order No.
3301 CG-S	Luminaire with CEWA GUARD monitoring and 20-digit address switch, without light source, with bezel white, plastic	40071342680


Accessories

Type	Order No.
Cube	Escape sign cube (242 x 227 x 242) acc. to ISO 7010 40071354670
Ceiling tube AP ¹⁾	Additional enclosure for surface mounting 40071342916
Bezel metal RAL 9010	40071345779

¹⁾ not applicable for cube mounting

Planning help for 3301 CG-S for E = 1.0 lx (0.5 lx)

Measuring level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m



Light distribution curve 3301 CG-S

Mounting height [m]	Types of mounting	L1	L2	L3	L4
2.5	Ceiling mounting	4.0 (5.3)	10.6 (13.8)	4.8 (6.2)	12.4 (16.0)
3.0	Escape route centre	4.0 (5.5)	11.0 (14.4)	4.9 (6.5)	13.0 (16.8)
4.0		3.6 (5.6)	11.0 (15.4)	4.8 (6.8)	13.4 (18.0)
5.0		0.1 (5.4)	10.6 (15.6)	4.3 (6.9)	13.6 (18.8)
6.0		0.1 (4.8)	9.0 (15.6)	0.1 (6.7)	13.0 (19.2)
7.0		0.1 (0.1)	2.0 (14.8)	0.1 (6.1)	11.6 (19.0)
3.0	Ceiling mounting	3.4 (4.4)	10.2 (13.2)	3.4 (5.4)	11.8 (15.2)
4.0	Room illumination	2.9 (4.4)	10.8 (14.2)	3.4 (5.4)	12.8 (16.6)
5.0		0.7 (4.4)	11.0 (15.0)	3.4 (5.4)	13.2 (17.6)
6.0		0.7 (3.4)	7.0 (15.4)	0.7 (5.4)	13.4 (18.2)
7.0		0.7 (0.7)	7.6 (15.4)	0.7 (4.4)	9.4 (18.8)