

SEI-T6128TI



Bullet IP, 4Mpxl, 2.8mm, ICR, WDR 120dB, LEDs 20-30mt, IP67/IK10, PoE, H.265, Advanced VCA A.

- 4 Megapixel IP Camera with real time video streaming
- Triple-streaming support
- H265 for high compression rate and stable stream control
- ONVIF protocol support
- Power-over-Ethernet support
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/3" CMOS (WDR)
Pixels - Total	2592 (H) x 1520 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.0028 lux @ F1.2
Lens Focal Length	2.8 mm
Horizontal Viewing Angle	102° (2.8mm)
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	WDR Pro 120dB
Advanced Video Analytics	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Scene change detection, masking of the camera lens, Tampering, Virtual line, Enter/Exit, Appear / Disappear, Audio detection, Face detection, network disconnect, IP address conflict, storage exception, Heatmap, People counting
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+, Triple Streaming
Video Resolution	1920x1080 (1080p), 1280x720 (720p), 4MP 2560 (H) x1440 (V), 3MP 2304 (H) x1296 (V)
ONVIF compliant	Profile S
Max. Users	4
Audio Inputs	None
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Dimensions (W x H x D)	74.5 x 74.5 x 167.5 mm - 2.93 x 2.93 x 6.59 In
Power Consumption (W)	7.5
Weight	0.46 kg - 1.01 lbs