

KPREMIUM1000

Part number: F101000

UPS on-line double conversion single-phase 1000VA



APPLICATION FIELDS



Input voltage (Vac)	230 Vac
Rack units	-
Output frequency (Hz)	50 - 60
Output voltage	230 Vac
Harmonic distorsion (%THD)	<3
Phase	Single
Power (kVA)	1
Power (W)	900
Technology	On-line
Installation	Tower
POWER (VA)	1000
Input frequency (Hz)	50 - 60
Input power factor	0,99
Wave form	Pure sine wave

Output power factor	0,9
Signalling	Low battery voltage, Overload, Operated batteries , Battery fault
Expandable backup time	yes
Connection	
IP rating	IP20
BACKUP TIME (min)	10
Overload	1s - 120%
By-pass	
Transfer time (ms)	0
Crest factor	3 ÷ 1
Standard provided equipment	Output cable
Protections	Excessive battery discharge, Overload, Short circuit, Thermal, Overvoltage
Audible noise at 1m (dBA)	<55
Working temperature (°C)	0 +40
Parallel connection	No
Communication	USB
Information on the display	Remaining backup time
EPO - Emergency power off	yes
Recharge time	7h to 90% of full capacity
Battery type	Sealed lead acid, maintenance-free
Standards	EN 61000-4-2, EN 61000-4-4, EN 62040-1, EN 61000-4-3, EN 61000-4-5
Warranty	2 Year
Package quantity (pieces)	1
Height (mm)	230
Width (mm)	144
Depth (mm)	350
Weight (Kg)	10