



Minidome IP AV, 4K(8MP), 3.6-12mm MOTOR., ICR, WDR, LEDs 20-30mt, IP66/IK10, PoE, VCA Basic

- 4K Resolution for super detailed images
- H265 for high compression rate and stable stream control
- Motorized varifocal lens for easy remote focusing
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- Vandal Resistant Dome (IK10)

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-V8320TI

Technical Specifications

Image Sensor	1/2.5" 8Megapixel progressive scan OmniVision CMOS
Pixels - Total	3840 (H)x 2160 (V), 25fps
Video Resolution	1280x720 (720p), 1920x1080 (1080p), 720x576 (D1), 3840 x 2160 (25fps)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.01 lux @ F1.2
Lens Focal Length	3.6~10 mm Motorized Autofocus
Horizontal Viewing Angle	80° (Wide) ~ 38° (Tele)
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR), 2D DNR (Off/On)
De-Fog	Off/On
Video Compression	H.264, H.265, MJPEG, Triple Streaming
ONVIF compliant	Profile S
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 OUT MIC
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP66
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-20°C ~ +50°C

Technical Specifications

Humidity	10 ~ 90%RH
Power Consumption (W)	6.5
Weight	1027 kg - 2264.15 lbs
Dimensions	Ø 150 mm - 5.91 In