

## SEC-8E1441IDTA



### Eyeball 4in1, 2MPxIs, 2.8-12mm Motor., ICR, WDR, 30mt LEDs, OSD, 12VDC, IP66

- 2 Megapixel Sony Exmor Sensor with superior low light performance
- 4-Hybrid Video Output HD-TVI/AHD/HD-CVI/960H
- 2.8 ~12mm varifocal motorized lens
- CoC Control Over Coaxial Cable OSD Control
- IP 66 Certification
- 1080p Full HD resolution over coax cable
- Day/Night feature, switching through photocell
- 3 Way Axis Gimbal, wall mountable

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2,8" CMOS Sony STARVIS STARLIGHT Progressive Scan
<b>Video Standard</b>	HD-TVI, CVBS (ITU-R-BT.470 PAL), HD-CVI, AHD
<b>Video Resolution</b>	1920x1080
<b>Horizontal Resolution</b>	600TVL on analogue output
<b>Col/B</b>	Auto / Color / B&W, IR-cut filter removable (ICR)
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.001 lux @ F1.2
<b>S/N Ratio</b>	>50 dB
<b>Lens Focal Length</b>	2.8 ~ 12 mm Motorized
<b>ELC</b>	Auto (1/50 ~ 1/100.000 sec.)
<b>WDR</b>	Yes
<b>BLC Back Light</b>	BLC / HLC / off
<b>AGC</b>	On/Off
<b>Digital Noise Reduction</b>	On/Off
<b>De-Fog</b>	Off/On
<b>OSD</b>	Yes, Multi Language with CoC (Control over Coaxial)
<b>White Balance</b>	ATW, Manual, AWC, Indoor, Outdoor
<b>Privacy zones</b>	16 zones, rectangle
<b>Motion Detection</b>	On/Off (4 Zones)
<b>Max. IR Distance</b>	30 m
<b>Optical Wavelength</b>	850 nm
<b>Video Outputs</b>	CVBS : 1.0 Vpp / 75 Ohm composite, 4 way Commutable, HD-CVI (BNC), HD-TVI (BNC), AHD (BNC)
<b>Mount</b>	Ceiling
<b>Protection Rating</b>	IP66
<b>Operating Humidity</b>	0 ~ 90%, non-condensing
<b>Operating Temperature</b>	-10°C ~ +50°C
<b>Supply Voltage</b>	12 VDC ±10%
<b>Power Consumption (W)</b>	9
<b>Weight</b>	0.800 kg - 1.76 lbs
<b>Dimensions</b>	Ø 131 mm - 5.16 In