

## SEI-T6127TI-N



**Bullet IP, 4MP, 2.8mm, H.265, ICR, dWDR, LEDs 20-30mt, IP67/IK10, POE, VCA Basic, WiFi**

- 4 Megapixel IP Camera with real time video streaming
- Support Wifi
- Triple-streaming support
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2.7" progressive scan CMOS
<b>Pixels - Total</b>	2560(H) x1440(V)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.011 lux @ F1.2
<b>Lens Focal Length</b>	2.8 mm
<b>Iris F-Number</b>	F 2.0
<b>S/N Ratio</b>	>50 dB
<b>Shutter Speed</b>	1 ~ 1/100,000 sec
<b>Max. IR Distance</b>	20/30m (according to scene reflexion)
<b>WDR</b>	D-WDR (Digital wide dynamic range)
<b>Intelligent Video Analytics</b>	Tampering, Motion Detection, Motion /Moved-Fixed Objects /Fence /Enter-Exit Area
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	H.264, H.265, Triple Streaming
<b>Video Resolution</b>	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps), 2048x1536 (25 fps), 5M 2592x1944 (20fps), 4M 2592x1520 (30fps)
<b>ONVIF compliant</b>	Profile S
<b>Max. Users</b>	4
<b>Motion Detection</b>	Yes
<b>Web Browser</b>	All major browsers are supported
<b>SD memory</b>	supports up to 128 GB capacity of micro SD memory
<b>Network Protocol</b>	HTTPS, SNMP, IPv4/IPv6, RTSP, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Wireless LAN</b>	Built-in WiFi module, IEEE-802.11b/g/n, wireless range : 80m, Security: WEP, WPA-PSK\WPA2-PSK
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30° C ~ +60° C
<b>Humidity</b>	less than 95%, non condensing
<b>Supply Voltage</b>	12 Vdc, PoE (IEEE 802.3af)
<b>Dimensions ( W x H x D)</b>	167.6 x 74.7 x 148.2 mm - 6.6 x 2.94 x 5.83 In
<b>Power Consumption (W)</b>	5
<b>Weight</b>	0.465 kg - 1.03 lbs