

**Bullet IP, 2MPxIs, 2.8mm, ICR, dWDR, LEDs 10-20mt, IP66/IK10, PoE.**

- 2 Megapixel IP Camera with Full HD 1080P real time video
- Triple-streaming support
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- IP 66 Certification
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-T4122TI-28

Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	1920(H) x 1080(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.1 lux @ F1.2
Lens Focal Length	2.8 mm
Iris F-Number	F= 1.6
Horizontal Viewing Angle	79°
S/N Ratio	>50 dB
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	10/20 m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264/ H.264H/ MJPEG, Triple Streaming
Video Resolution	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps)
ONVIF compliant	Profile S
Max. Users	3
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-20°C ~ +50°C
Humidity	10 ~ 90%RH
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	4.5
Weight	0.333 kg - 0.73 lbs
Dimensions	∅ 70 x 156 mm - 2.76 x 6.14 In