

SEI-T6328TI



Bullet IP, 4Mpxl, 5-50mm MOTOR., ICR, WDR 120dB, LEDs 70-90mt, IP67/IK10, POE, H.265+, Face Detection, ADVANCED VCA A.

- 4 Megapixel IP Camera with real time video streaming
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-T6328TI



Technical Specifications

Image Sensor	1/3" CMOS (WDR)
Pixels - Total	2592 (H) x 1520 (V)
Video Resolution	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288) , 4MP (2592x1520)
Scanning System	Progressive
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity Colour	0.05 Lux@F1.6
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	5 ~ 50 mm Motorized @ F1.6
Iris Operation	Auto iris (DC)
Shutter Speed	1/3 ~ 1/100,000 sec
Max. IR Distance	70/90 m (according to scene reflexion)
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, Triple Streaming, H.264+, H.265+
ONVIF compliant	Profile S
Advanced Video Analytics	Advanced video Analytics A: Area intrusion/line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 CH, Line in
Audio Outputs	1 CH, RCA
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)

SEI-T6328TI



Technical Specifications

Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions (W x H x D)	279.5 x 100.3 x 88.9 mm - 11 x 3.95 x 3.5 In
Power Consumption (W)	10
Weight	1.04 kg - 2.29 lbs