

SEI-P8140-TI-360



Panoramic 360° IP, 4x2MP=8MP ICR, dWDR 120dB, STARLIGHT, LEDs 15mt, IP66/IK10, POE, H.265, Advanced VCA A.

- 8 Megapixel IP Panoramic Camera with real time video streaming
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- Built-in SD card reader for message recording in case of no answer
- Block of access after multiple login failed tentatives
- System Log preserved after system reset
- Request to modify password at first login
- AES128 encrytion on local SD recording

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	3840 (H)x 2160 (V), 25fps
Video Resolution	Stream 0, Panoramic View: 3840x2160, 2560x1440, 1920x1080, Stream 1,2,3,4 : 1920x1080, 1280x760, 720x480
Scanning System	Progressive
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Sensitivity Colour	0.005Lux @ F1.6
Sensitivity B/W	0 Lux LED IR on
Iris Operation	Auto, Manual, Fixed Iris
Lens Focal Length	4 mm
Shutter Speed	1 ~ 1/100,000 sec
Max. IR Distance	25 m
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+
ONVIF compliant	Profile S, Profile G
Advanced Video Analytics	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Motion Detection, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
Max. Users	15
SD memory	up to 256 GB
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 CH, Line out
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485

Technical Specifications

Supply Voltage	PoE+ (IEEE 802.3at), 24 Vac / 24 Vdc ±10%
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30°C ~ +55°C
Humidity	less than 95%, non condensing
Power Consumption (W)	25
Weight	3.26 kg - 7.19 lbs
Dimensions	Ø 273 mm - 10.75 In