

GS331

Dispositivo di prova per i sensori piezo

Glass Break Tester

The tester GS331 is used to verify the operation of the glued-on-glass glass break detectors GS300/310. You test the detector by pressing the tester against the window. A noise will be heard simulating a glass breakage. It is recommended to test the glass break detectors before and after the installation.

Please note that this is not a range tester.



Dettagli

- Automatic switching off
- Battery display via LED
- Test display via LED

GS331

Dispositivo di prova per i sensori piezo

Specifiche tecniche

Generale

Gruppo accessori	Sensori Rottura vetri
Tipo	Parti di ricambio

Elettrico

Tensione di esercizio	6 to 10 VDC
Consumo attuale	1 mA nominal at 12 VDC (standby) 60 mA nominal at 12 V (alarm)

Fisico

Physical dimensions	120 x 60 x25 mm
Peso netto	150 g

Battery

	9 V
--	-----

Battery life

	Approx. 8 hours operating time or 3000 activities (each 10 s long)
--	---

System indicator

	Green LED blinks at pushed button mode
--	--

Battery indicator

	Red LED
--	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:31