

## PM812N-G2

### Power supply switch mode, 12 VDC, 1.4 A, EN Grade 2

#### Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 Grade 2 and Environmental Class II, requiring 18Ah standby battery capacity.

#### **Protection**

Comprehensive protection is built-in as standard including mains transient filtering, electronic output overload protection and fuses on the load and battery outputs.



#### **Details**

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamperswitch
- Protection against reverse battery connection
- Thermal protection of power circuitry
- LED's for comprehensive diagnostics
- Powder coated steel housing
- EN50131-6:2008 Grade 2 Type A certified

# PM812N-G2

## Power supply switch mode, 12 VDC, 1.4 A, EN Grade 2

### **Technical specifications**

General	
Fuse(s)	Load: F1.6 A, Batt: F1.6 A
Deep discharge	Battery disconnect @ 10.6 V battery terminal
protection	voltage
Protection	Reverse battery connection protection
Electrical	
Mains input	100 to 240 VAC
Output	
Power output voltage	13.8 VDC
Output ripple	<400 mV pk - pk max. @ rated voltage
Power output current	1.5 A
mains	
Battery	
Max. Battery capacity	18 Ah 12 V
Power output current battery	12 hours 1.5 A with 18 Ah battery
Battery recharge time	< 72 hours to 80%
Physical	
Physical dimensions	330 x 275 x 80 mm (W x H x D)
Net weight	3.3 kg (without battery)
Colour	White
Form factor	Steel cabinet
Environmental	
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Regulatory	
EN50131 Grade	Grade 2
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN50131 Grade 2
Housing (steel) pov	wder coated
	1.2 mm
Certifications	
	EN50131-6:2008 Grade 2 Type A
	Environmental Class II



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.