



NetKey® Patch Cord

NK5EPC3MORY

Netkey copper patch cord, category 5e, 3 meters, orange UTP cable.

 **Discontinued - Limited Stock**

Suggested Replacement Parts:

NK6PC3MORY

NKU5EPC3M

Note: It is the buyer's responsibility to determine if the suggested replacement part is suitable for your application and intended use.

Specifications

Application	Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), and 1000BASE-T (Gigabit Ethernet), 155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM, Token Ring 4/16, Voice over internet protocol (VoIP)
Product Type	Patch Cord
Conductor Gauge (AWG)	24
Conductor Gauge (kcmil)	0.4
Sub Brand	NetKey®
Performance Level	Category 5e
Conductor Type	Stranded
Cable Construction	U/UTP
Patch Cord Type	Unshielded
Overall Length (m)	3
Maximum Operating Temperature (°C)	60
Minimum Operating Temperature (°C)	-10
Color	Orange
Flammability Rating	CM
Standards Met	ANSI/TIA-568-C.2 Category 5e and ISO 11801 Class D, ANSI/TIA-568-C.2 and ISO 11801 Category 5e, ANSI/TIA-1096A (formerly FCC Part 68), IEC 60603-7, IEEE 802.3af/802.3at and proposed 802.3bt type 3 and type 4 PoE applications, cULus Listed; UL 1863 and CAN/CSA-C22.2 (UL File E129886), CM rated 802.3af / 802.3at and 802.3bt type 3 and type 4, UL 1863, CSA standard C22.2, RoHS Compliant
IEC Variant	60603-7
PoE Compatibility	PoE
Plug Type	Meets IEC 60603-7
RapidID™ Enabled	No

Specifications (continued)

Part Features	100% performance tested, Patented tangle free latch, Identification and Variety of color and lengths available
---------------	--

Packaging Detail

UPC	07498331487
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0240
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.2397